

Customer Information:

| First Name: | Last Name: |
|-----------------|------------|
| Street Address: | City: |
| State: | Zip Code: |
| Phone: | E-mail: |

Mustang Factory Wiring Conversion for Holley EFI

Select the applicable year, engine, and transmission for your build from the options below.

| Year: Engine: Transmis | 87-93 94-95 3.8L 5.0L/5.8L (Pushrod) ssion: 5/6 Speed Manual | 96-98 4.6L/5.4L AOD/AODE/4R70W | 99-04 5.0L/5.2L Coyote / Automatic | /Voodoo | | |
|--|--|--------------------------------------|---|--|--|--|
| NOTE: If harnesses supplied are from a different model year, engine, and transmission than your build selections, you must notate the differences in the Customer Notes section at the bottom of the form. | | | | | | |
| 1. Ha | ave any other harnesses been modified? | | Yes | 🗌 No | | |
| If yes, what has been modified/removed: | | | | | | |
| Functions to retain: | | | | | | |
| Hi Fu Fi Ai Lo Lo | ow Speed Fan Control igh Speed Fan Control iel Pump Control r Conditioning ow Coolant Sensor (sensor located in overflow ta ow Oil Sensor nti-Lock braking system NOTE: For items 2 through 5, if you selected yes, a relay | nk) | Yes Yes Yes Yes Yes Yes Yes Stor it to function. | No No No No No No No No | | |
| Gauges to retain: | | | | | | |
| 10. Ta 11. Co | peedometer achometer polant Temperature il Pressure NOTE: If a gauge is not listed, that means its signal feed and will function so long as all the other remaining facto | - | | No No No No | | |
| | <u>Miscella</u> 2v switched lead wire to trigger the Holley on & c ODE/4R70W overdrive switch control | | Yes Yes | ☐ No ☐ No | | |

Customer Notes: